

Fish Zircon Range

Model: FZ18 - Datasheet

Key Features

- Foodsafe stainless steel exterior and interior
- Radiused, easy clean, interior based corners to reduce potential dirt traps
- CoolSmart controller is designed for easy operation and features clear digital display
- Designed and engineered to operate efficiently up to a 43°C ambient, this exceeds Climate Class 5
- Self closing doors minimises temperature gain, reducing energy consumption
- Precision injected, high density 75mm polyurethane insulation. Provides excellent thermal efficiency with low GWP (Global Warming Potential) and zero ODP (Ozone Depletion Potential)
- Cabinet designed and fitted with low level heavy-duty, non-marking swivel castors with braked to front, to enable easy positioning and mobility through a standard door opening
- Barrel locked doors for added security

- 7 polypropylene containers for easy cleaning, lightness and durability, each with a removable slime tray
- Interior lined, piped and drained through the base into unit compartment exiting to rear - drain should be connected to a permanent waste or suitable container
- Easy to access bottom mounted refrigeration system

Options

- Additional polypropylene trays
- 25mm adjustable levelling feet

Variant	Temp	Storage
FZ18	-2/+2°C	Fish

Dimensions

	FZ18
External (mm):	H1906 W595 D722
Internal (mm):	H1250 W445 D598
Door Opening (mm):	D1276
Packed:	H1920 W630 D730
Weight: Add 5kg per product for packaging	122kg

Important Information

	FZ18
Capacity: kg	114
Construction	
Exterior	0.7mm stainless steel
Interior	0.6mm stainless steel
Door	0.7mm stainless steel ext 0.6mm stainless steel int
Power Supply	220V/240V 50Hz/1Ph 13 amp plug
Power Input	
Start Up	10.7 amps
Running	2.5 amps
Compressor HP	1/4
Energy Consumption (Tested to EN153) in 24hrs	2.21kW
Heat Rejection (Evaporating at -10°C in 32°C ambient)	565 watts
Refrigerant	R134a
Defrost	Auto off- cycle
Insulation ODP Zero Polyurethane	75mm
Noise Output	50.0dBA
Fittings Shelves	7 polypropylene trays



Bryggen Road, North Lynn Industrial Estate
King's Lynn, Norfolk PE30 2HZ

T +44 (0) 1553 817000

F +44 (0) 1553 817111

Spares +44 (0)1553 817017

E info@williams-refrigeration.co.uk

W www.williams-refrigeration.com

Allow minimum of 500mm above cabinet for maintenance and ventilation. All refrigeration equipment requires adequate ventilation for efficient and effective performance. Williams are committed to a policy continuing product development and innovation and as such, we reserve the right to change product specifications stated without prior notice.

V6 - July 2010